

## Sustain 5.7mm

---

Collection:	<b>SUSTAIN</b>	
Nominal Dimensions:	<b>8 in w x 51 in l   8.00</b>	
Actual Dimensions:	<b>in w x 50.79 in l</b>	
Overall Thickness:	<b>0.224 in</b>	
Edge Profile:	<b>Micro-Bevel</b>	Metric
Installation Type:	<b>Click</b>	<b>20 cm w x 129 cm l   20.32</b>
Installation	<b>Floating</b>	<b>cm w x 129.01 cm l   5.7 mm</b>

### Packaging:

---

Pieces per Carton	<b>9 pcs</b>	
Area per Carton	<b>25.36 sq ft</b>	<b>2.36 sq m</b>
Weight per Carton	<b>38.427 lbs</b>	<b>17.43 kg</b>

### Coordinating Products:

---

PVC-Free: Pivot, Observe, Experiment

### Performance + Testing:

---

Static Load (ASTM F970) Resistance to Heat (ASTM F1514)	<b>Passes (Modified), *1000 lbs</b>	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Resistance to Light (ASTM F1515)	<b>Passes</b>	
Smoke Density (ASTM E662, Flaming Mode) Radiant Panel (ASTM E648)	<b>Passes</b>	
Coefficient of Friction (ASTM D2047, Slip Resistance)	<b>Passes, Class I</b>	
	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

### Warranties:

---

[15 Year Commercial Limited Warranty](#)

### Material Health & Environmental Certifications

#### Health & Wellbeing

Material Ingredient Transparency

Greenhealth Approved | Yes  
Health Product Declaration (HPD) | 1000 ppm Disclosure  
Declare | LBC Compliant

Indoor Air Quality

Greenguard Gold | Certified

#### Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, And ISO 21930

Embodied Carbon (Cradle to Gate) Total

9.7 Kg Co<sub>2</sub>/M<sup>2</sup>

Recycled Content

25% (Pre-Consumer 0% | Post-Consumer 25%)

#### Global Product Assessment

Environmental Guarantee\* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Resilient Within The United States And Canada At No Cost to The Customer.

Country of Origin | Imported

#### WELL V2 Contribution Credit

X01 Fundamental Material Precautions  
Part 1: (C): Restrict Asbestos Precondition

**Absence of Asbestos**

X08 Hazardous Material Reduction  
Part 1: Limit Hazardous Materials Optimization

**Absence of Heavy Metals**

X10 Volatile Compound Reduction  
Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

**Absence of Halogenated Flame Retardants**

X10 Volatile Compound Reduction  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

**Ortho-Phthalates Free**

X11 Long Term Emissions Control  
Part 2: Flooring Optimization

**Green Guard Gold Certified**

X14 Material Transparency  
Part 1: Promote Ingredient Disclosure Optimization

**Health Product Declaration (HPD) | 1000 Ppm Disclosure**

#### Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

**Health Product Declaration (HPD) | 1000 Ppm Disclosure**

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

**Greenguard Gold Certified**

#### Additional Information

#### [Installation Guidelines](#)

#### [Maintenance](#)

#### [Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supplyand/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.